




APPENDIX A Revision A		TRAILER MOUNTED SUPPORT SYSTEM PRODUCT DATA SHEET	
Company		DHS Systems LLC	
Part Number or NSN		TG201-0005G	DRASH HP-2C/338, OD Green, Analog
Specifications as applicable			
Safety and Mobility Certification by Military Test Center			
Trailer			
Stowage Components included with trailer	NA		
Cargo Volume Stowage, For shelter and accessory components In cubic feet	58 cu. ft.		
Physical Dimensions for trailer Height Width Length	6.5 ft H 7.2 ft W 14.75 ft L		
Recommended Prime Mover Vehicle	HMMWV	Requires a vehicle capable of towing a 4,200 lb. trailer.	
Empty GWW	NA		
Tongue Weight	344 lb.		
Tire Type and Size	Radial	Two 37 x 12.50 x 16.5 LT Goodyear Wrangler R/T II, Load Rating C bias-ply, run-flat tires.	
Fuel Tank Capacity	26 gal		
Generator			
Nominal Output in kW, Volts AC, Hertz, Phase	33kW	120/208VAC, 60 Hz, 3-Phase.	
Operating Environment	All	Operating Range: -50 °F to +140 °F.	
Engine type	Diesel	Four cylinder, turbo-charged, liquid cooled, direct injection, 1800 RPM	
Fuel Type	Diesel	Can also use JP8 or JP5.	

Fuel Consumption (AC Compressor On) At 25% load At 50% Load At 75% Load at maximum output	NA NA NA 2.65	
Noise in DB at 25 feet (AC Compressor On) At 25% load At 50% load At 75% Load At maximum rated load	NA NA NA 76 dB	
Heater		
Nominal Output in BTU's	NA	
Electric Requirement Volts/Amps	NA	
Air Conditioning		
Maximum Cooling Capacity in BTU's		96,000 BTU/hr
Maximum Heat Output Capacity in BTU's		2 stage heat 92,000 BTU/hr electric heat. 80,000 BTU/hr fuel fired 
Refrigerant Type	R407-C	
CFM Air Flow	3,000 CFM	
Air Duct Diameter	4 Ducts	Two 14 in Supply Two 14 in Return
Power Requirements in kW, VAC, HZ, Phase	28kW	208 VAC, 60 Hz, 3-phase.
Special/Additional Features:	<p>The HP-2C/338 Trailer provides three primary features for the end user of a smaller DRASH shelter: cargo space, environmental control and electrical power. It has a 58 cubic foot cargo area, includes a 26-gallon fuel tank and comes with a 33kW Genset and an 8-ton ECU.</p> <p>INCLUDES: Drip Berm (P/N: T295188), qty. = 1 Trailer Electrical Set (P/N: T2-95230), qty. = 1 Trailer Push Package (P/N: TR351G), qty. = 1 Auxiliary Fuel Kit (P/N: TG430-6001-PH), qty. = 1 Air Supply Duct (P/N: T291230), qty. = 2 Air Return Duct (P/N: T291432), qty. = 2 Fire Extinguisher, 5lbs, (P/N T295175), Qty. = 1</p>	